

Technical Information

Adhesin A 1128-21



Type of adhesive emulsion based adhesive containing plasticizer

Field of Application Bags and sacks Industry
Bottom glueing of unprinted bags made of paraffinated paper

Product Specifications

Test method

Viscosity 250.000 \pm 50.000 mPa.s Brookfield RVT 7/10/23 , ISO 2555

pH-Value 7,0 \pm 1,5 ISO 976

Adhesin A 1128-21 is currently undergoing extensive practical tests and still at an experimental stage. Technical data may change.

Product Properties

Film Adhesin A 1128-21 forms a dry, tough film.

Application By means of segment, roller as well as screen roller. Most suitable processing temperature: 18 - 25 °C.

Dilution Adhesin A 1128-21 can be diluted with cold water if required.

Cleaning Uncured adhesive residues as well as dried adhesive films can easily be removed with water. Wetting agents accelerate the cleaning process.

Disposal See Safety Data Sheet

Protective Measurements See Safety Data Sheet

Storage Conditions/ Shelf life

In closed original packaging 6 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

Düsseldorf, January 2007

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad
Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050
Email: info@van-asperen.nl Web: www.van-asperen.nl



Technologies
Industrial Adhesives