Technical Information
Purmelt Cleaner 2

van Asperen
K L E E F S T O F F E N

Type of adhesive	Purmelt Cleaner 2 is a cleaner hotmelt adhesive for polyurethane hotmelt adhesives application
Field of application	Purmelt Cleaner 2 is used for cleaning of application equipments, melting systems and such like which are used for polyurethane hotmelt adhesives applications. Purmelt Cleaner 2 convert the reactive components of the poly-urethane hotmelt adhesive, to rule out further crosslinking processes.

Product specification		**Test Method**
Density	0,95 $\pm$ 0,05 g/cm³	
Softening point	72 $\pm$ 4 °C	R&B
Viscosity	6.500 $\pm$ 500 mPa.s at 130°C	Brookfield

Viscosity depending on the temperature:

Processing advice	At application processes with melt pot granulated Purmelt Cleaner 2 is used. At working with drum melt units Purmelt Cleaner 2 is avail-able in equivalent hobbocks or drums. Purmelt Cleaner 2 is bluish coloured to faciliate the cleaning process. Commonly Purmelt Cleaner 2 is used with the same application temperature as the polyurethane hotmelt which was applied during the working process (approx. 90 - 140 °C).
Storage	At room temperature in closed rooms at least storable for 12 months.
Protective Measures	see Safety Data Sheet

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.
Düsseldorf, March 2000

(Henkel)
Technologies
Industrial Adhesives