

# Technical Information

## Adhesin A 2335



**Type of adhesive:** emulsion-based adhesive with excellent lay-flat properties

**Field of application: Lamination:**

For lamination of paper with carton where a good stay-flat property is required.

**Mailing:**

Most suitable for e.g. Cheshire-addressograph.

**Product specification:**

**Viscosity:** 850  $\pm$  200 mPa.s

**Test Method**

Brookfield RVT, 2/20/23  
ISO 2555

**pH-value:** 6,5  $\pm$  1

ISO 976

**Properties:**

**Film:** soft, tacky and transparent

**Processing:**

**Application:** by means of rollers, segment and nozzle.  
Most suitable working temperature 18 - 25 °C.

**Dilution:** Adhesin A 2335 can be diluted with cold water if required.

**Cleaning:** Uncured adhesive residues can easily be removed with water. Wetting agents increase the cleaning process..

**Disposal:** see Safety Data Sheet

**Protective Measures:** see Safety Data Sheet

**Storage Conditions/**

**Shelf Life:** In closed original packaging 6 months from date of production.  
Optimum storage temperature: 15 - 25 °C, protect from frost.  
Close containers thoroughly after use.

The Information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.  
Düsseldorf, December 2001

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad  
Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050  
Email: [info@van-asperen.nl](mailto:info@van-asperen.nl) [www.van-asperen.nl](http://www.van-asperen.nl)



**Technologies**  
Industrial Adhesives