

Technical Information

Adhesin A 2354



Type of adhesive	synthetic resin dispersion, containing plasticizer	
Field of application	Low viscous and fast setting adhesive for the packaging industry for unlacquered materials. General bonding of paper	
Product specifications		Test method
Viscosity	1.800 \pm 200 mPa.s	Brookfield RVDV 3/20/23, ISO 2555
pH-value	4,5 \pm 1,0	ISO 976
Product properties	Adhesin A 2354 forms an elastic film. The adhesive complies with FDA 175.105.	
Processing		
Application	by means of nozzle, segment, roller or disc most suitable working temperature is 18 – 25 °C	
Dilution	Adhesin A 2354 can be diluted with cold water if required.	
Cleaning	Uncured adhesive residues can easily be removed with water. Wetting agents accelerate the cleaning process.	
Disposal	See Safety Data Sheet	
Protective Measures	See Safety Data Sheet	
Storage conditions / Shelf Life	In closed original packaging 6 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost. Close packaging thoroughly after use.	

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

Düsseldorf, March 2004

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad
Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050
Email: info@van-asperen.nl www.van-asperen.nl

