## Technical Information Dela S 264



Type of adhesive dextrin-based adhesive

Field of application labelling

Product specifications Test method

Viscosity thickflowing, softpasty

pH-value 4,0 <u>+</u> 1,0 DIN 53785

Product properties Dela S 264 is a dextrin-based adhesive for labelling of untreated glass

bottles, jars and tins. The glue provides a high wet tack and a relatively

long open time. Dela S 264 is pumpable.

Processing

Application fully automatical labelling machines working with rotation- or straight feed

principle

Dilution Dela S 264 is ready for use and should not be diluted.

Cleaning Uncured and cured adhesive residues can easily be removed with water.

Wetting agents accelerate the cleaning process.

Disposal see Safety Data Sheet

Security advices see Safety Data Sheet

Shelf life 6 months in closed original packaging

Storage conditions optimum storage temperature: 15 - 25 ° C, protect from frost.

After use close packaging thoroughly.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

Düsseldorf, April 1997

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050

Email: info@van-asperen.nl Web: www.van-asperen.nl



DS264 E.DOC Page 1 Status: April 1997