

Purmelt Cleaner 3

Cleaning Hotmelt for Polyurethane Adhesives



Issue: 05.04.2006

Product Description / Application Areas

Purmelt Cleaner 3 is a Cleaning agent for all Macroplast QR grades in the uncured state applied by rollers. It has very good cleaning properties and wetting characteristics.

Technical Data

Density:	1,22 g/cm ³
Softening point (Kofler):	approx. 50 °C
Application temperature:	80 – 140°C

Instructions for Use

Preliminary remark

Prior to application it is necessary to read the Safety Data Sheet for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labelling, the relevant precautions should always be observed.

Application

Commonly Purmelt Cleaner 3 is used with the same application temperature as the polyurethane hotmelt which was applied during the working process.

Storage

Shelf-life 12 months if stored in a cool and dry place

Packaging

Hobbock

15 Kg

**Hazard Indications/
Safety Recommendations/
Transport Regulations**

see Safety Data Sheet

Important

The above data, particularly the recommendations for application and use of our products are based on our knowledge and experience. Due to the different materials and conditions of application which are beyond our knowledge and control we recommend strongly to carry out sufficient tests in order to ensure that our products are suitable for the intended processes and applications. Except for willful acts any liability based on such recommendations or any oral advice is hereby expressly excluded.

This Technical Data Sheet supersedes all previous editions.