



3M™ Single Coated Line Set Tape 3336

Product Data Sheet

December 2008
Supersedes: New

Product Description

3M Single Coated Line Set Tape 3336 is a UV resistant bi-axially oriented polypropylene (BOPP) tape coated with a solvent acrylic adhesive that combines resistance to both high and low temperature ranges.

3M 3336 replaces cloth duct tape, lasts longer and will not delaminate with age. The tape provides easy application and superior performance and durability over a wide range of temperature and environmental conditions. The black version works well on black foam pipe used in line sets. The silver version is used for sealing of flexible air ducts and air connectors in Heat, Ventilation and Air Conditioning (HVAC) applications.

Physical Properties

Adhesive Type	Acrylic
Backing	Polypropylene (BOPP)
Colour	Silver and Black
Thickness	0.076 mm

Performance Characteristics

Peel Adhesion (PSTC 101)	11.4 N/25mm
Tensile Strength (PSTC 131)	98 N/25mm
Elongation (PSTC 131)	150%
Temperature Performance	127 °C

Storage	Store in clean dry place. Temperature of 21 °C and 50 percent relative humidity are recommended.
Shelf Life	3M Single Coated Line Set Tape 3336 has a shelf life of 12 months from date of dispatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity
For Additional Information	To request additional product information see address below.
Important Notice	<p>All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application.</p> <p>All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law</p>

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.
This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.

3M Nederland B.V.
Postbus 193, 2300 AD LEIDEN
Tel: +31 (0) 71 54 50 450