



Scotch-Mount™

4430 Double Coated Foam Tape

Product Data Sheet

Updated : October 1993
Supersedes :

Product Description

4430 is a white double coated synthetic foam tape with a high tack acrylic adhesive. This tape has a plain white paper liner.

Physical Properties

Not for specification purposes

Adhesive Type	Acrylic	3M ref :
Foam Core	Synthetic	Foam Density 560 kg/m ³
Thickness (ASTM D-3652)		
Tape	0.8 mm ± 0.1mm	
Release Liner	White Paper	
Tape Colour	White	
Shelf Life	12 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	

Performance

Characteristics

Not for specification purposes

Peel Adhesion to Stainless Steel 90° peel @ room temp, 72 hr dwell, jaw speed 300mm/min	20 N/10mm	
Static Shear Strength weight held for 100 hours to stainless steel with ½ sq in (3.23 sq cm) overlap	1000g @ 20°C 500g @ 70°C	
Temperature Performance		
Continuous	70 °C	
Intermittent	100 °C	

Date : October 1993
4430 Double Coated Foam
Tape

Additional Product Information

This product is suitable for plasticised PVC BUT IS NOT SUITABLE FOR LOW SURFACE ENERGY PLASTICS.

Application Techniques

1. Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure develops better adhesive contact & thus improves bond strength.

2. To obtain optimum adhesion, the bonding

surfaces must be clean dry and well unified. A typical surface cleaning solvent is isopropyl alcohol & water. Use proper safety precautions for handling solvents.

3. Ideal tape application temperature range is 21°C to 38°C (70°F to 100°F).

Initial tape application to surfaces at temperatures below 10°C (50°F) is not recommended because the adhesive becomes too firm to adhere readily. However once properly applied low temperature holding is generally satisfactory.

Applications

Bonding cable trunking within cabinets or on furniture.

Point of sale bonding applications using board, paper and most plastics.

Signing applications - low performance.

Furniture trim bonding.

Cable clips & air freshener, bonding.

3M and Scotch-Mount are trademarks of the 3M company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Specialty Tapes & Adhesives

© 3M United Kingdom PLC 1996

3M United Kingdom PLC
3M House,
28 Great Jackson Street,
Manchester,
M15 4PA

Customer Service :

Tel 0161 236 8500
Fax 0161 237 1105

3M Ireland
3M House, Adelphi Centre,
Upper Georges Street,
Dun Laoghaire, Co. Dublin,
Ireland

Customer Service :

Tel (01) 280 3555
Fax (01) 280 3509