

Technical Information

Adhesin A 7020-21



Type of adhesive Emulsion-based adhesive

Field of application **Bookbinding**
Primer for two-shot systems

Product specification

Viscosity 1.200 - 1.800 mPas

Test Method

Brookfield RVT, 2/20/23
ISO 2555

pH-value 3,0 - 5,0 ISO 976

Adhesin A 7020-21 is currently undergoing extensive practical test and is still at an experimental stage. Technical data may change.

Product properties

Film Adhesin A 7020-21 forms an elastic film with good adhesion to Disp-O-Fusion F 260.

Processing

Application By means of rollers, very thin
Most suitable working temperature: 18 - 25 °C

Cleaning Uncured adhesive residues as well as dried adhesive films can easily be removed with water. Wetting agents increase the cleaning process

Disposal see Safety Data Sheet

Protective Measures see Safety Data Sheet

Storage Conditions/

Shelf Life In closed original packaging 6 months from date of production. Optimum storage temperature: 15 – 25 °C, protect from frost. Close containers thoroughly after use.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad
Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050
Email: info@van-asperen.nl Web: www.van-asperen.nl

