Technical Information Adhesin A 7093



Type of adhesive synthetic resin dispersion, free of plasticizers

Field of application Packaging Industry

Bonding of unlacquered and lacquered paper and cardboard. Lamination of rigid

and soft PVC-films with absorbent materials.

Diaphragm glueing. Bookbinding

Casing-in of books into covers made from PVC, general bondings of PVC-

materials with paper or cardboard.

Billboarding

Primer for billboards made of metal or aluminium

Product specifications

Viscosity 2.400 <u>+</u> 500 mPa.s

Test Method

Brookfield RVT 3/20/23,

ISO 2555 ISO 976

pH - value $5,0 \pm 1,0$

Product properties Adhesin A 7093 is a fast setting adhesive and corresponds to the recommendation

XIV of BgVV

Film elastic, resistant against plasticizers, high heat resistance

Processing Application

roller, segment, nozzle, disc

Most suitable processing temperature: 18 - 25 $^{\circ}$ C.

Dilution Adhesin A 7093 can be diluted with cold water if required.

Cleaning Uncured adhesive residues as well as dried adhesive films can easily be

removed with water. Wetting agents increase the cleaning process.

Disposal see Safety Data Sheet

Protective Measures see Safety Data Sheet

Storage Conditions/

Shelf life

In closed original packaging 6 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost. Close containers carefully after use.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

Düsseldorf, August 2002

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad

Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050 Email: info@van-asperen.nl www.van-asperen.nl



A7093e.doc Page 1 Status: 08 / 2002