

Technical Information

Adhesin A 7157-24



Type of adhesive	Water based dispersion
Field of application	Manufacture of envelopes Adhesive for PS and treated OPP film

Product specifications	Test Method
Viscosity	1.800 – 2.900 mPa.s Brookfield RVT, 3/20/23, ISO 2555
pH-value	7,0 – 10,0 ISO 976

Adhesin A 7157-24 is currently undergoing extensive practical tests and still at an experimental stage. Technical data may change.

Product properties

Film	soft elastic
-------------	--------------

Processing

Application	Winkler 102, 202 and Classic Most suitable processing temperature : 18 – 25 °C.
Dilution	A 7157-24 can be diluted with cold water if required.
Cleaning	Uncured adhesive residues can easily be removed with water. Dried adhesive films can be removed with our cleaning agent A 1920.
Disposal	see Safety Data Sheet
Protective Measures	see Safety Data Sheet
Storage Conditions/ Shelf Life	In closed original packaging 3 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost. Close containers thoroughly after use.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.
Düsseldorf, December 2003

