Technical Information Adhesin A 7214-21



Test Method

ISO 2555

ISO 976

Brookfield RVT, 4/20/23,

Type of adhesive: emulsion-based adhesive, containing plasticizer

Field of application: Graphic industry

Casing in of book blocks, side glueing of books.

Product specifications:

Viscosity: $3,000 \pm 500 \text{ mPa.s}$

pH-value 4.5 ± 1.0

Product properties: Adhesin A 7214-21 is a fast setting, solvent free

adhesive

Adhesin A 7214-21 is suitable for seam and surface glueing. Besides excellent stay-flat properties. Adhesin A 7214-21 provides clean machineability as

well as good cleaning properties.

Film: Soft elastic, reversible

Processing: Processing can be effected either by means of a bottle

or a circulating pump system.

Application: By means of segment, nozzle, roller.

Most suitable processing temperature: 18-25° C.

Dilution: The product can be diluted with cold water if required.

Cleaning: Uncured adhesive residues can easily be removed

with water

Disposal: See Safety Data Sheet.

Protective Measures: See Safety Data Sheet.

Storage Conditions/

Shelf Life:

In closed original packaging 6 months from date of production. Optimum storage temperature: 15 - 25 °C,

protect from frost. Close containers carefully after use.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

This is a new product, the technical specification could change.

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad

Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050 Email: info@van-asperen.nl Web: www.van-asperen.nl



