

# Technical Information

## DISP-O-FUSION A 7621



<b>Type of adhesive</b>	emulsion – based adhesive	
<b>Field of application</b>	Bookbinding Primer for two-shot systems	
<b>Product specification</b>		<b>Test Method</b>
Viscosity	1.150 ± 250 mPa.s	Brookfield RVDV 2/20/23 ISO 2555
pH-value	6,0 ± 1,0	ISO 976
<b>Product Properties</b>		
Film	DISP-O-FUSION A 7621 forms an elastic film with good adhesion to polyurethane hotmelts.	
<b>Processing</b>		
Application	by means of rollers, very thin Most suitable working temperature: 18 – 25 °C.	
Cleaning	Uncured adhesive residues as well as dried adhesive films can easily be removed with water. Wetting agents increase the cleaning process.	
Disposal	see Safety Data Sheet	
<b>Protective Measures</b>	see Safety Data Sheet	
<b>Storage Conditions/ Shelf Life</b>	In closed original packaging 6 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost. Close containers thoroughly after use.	

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.  
Düsseldorf, October 2003