

Technical Information

Adhesin A 7813

van Asperen
KLEEFSTOFFEN

Type of adhesive	synthetic resin dispersion	
Field of application	Packaging Industry Low viscous and fast setting adhesive for the packaging industry for lacquered and unlacquered materials. General bonding of paper.	
	Bags and Pouches Bonding of longitudinal seam of unlacquered and lacquered papers.	
Product specifications		Test Method
Viscosity	1,700 ± 300 mPa.s	Brookfield RVT, 3/20/23, ISO 2555
pH-value	6±1	ISO 976
Product properties	Adhesin A 7813 forms an elastic film. The adhesive complies with FDA 175.105.	
Processing Application	By means of nozzle, segment, roller or disc. Most suitable processing temperature: 18-25 °C.	
Dilution	The product can be diluted with cold water if required.	
Cleaning	Uncured adhesive residues can easily be removed with water	
Disposal	See Safety Data Sheet.	
Protective Measures	See Safety Data Sheet.	
Storage Conditions/ Shelf Life	In closed original packaging 6 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost and do not store below 10°C. Close containers carefully after use.	

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad
Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050
Email: info@van-asperen.nl www.van-asperen.nl

