

Technical Information

Adhesin A 8162-22



Type of adhesive aqueous polymer dispersion without plasticizers

Application field **Graphic Industry**
Adhesive for removeable bonding of papers.

Product specifications

Test Method

Viscosity 250 \pm 100 mPa.s

Brookfield RVT, 2/20/23,
ISO 2555

pH-value 8,5 \pm 0,5

ISO 976

Adhesin A 8162-22 is currently undergoing extensive practical tests and still at an experimental stage. Technical data may change.

Product properties Adhesin A 8162-22 provides a safe initial tack and final bond strength.

Film white, not surface tacky

Application Stir the adhesive before use.
By means of nozzle.
Most suitable processing temperature: 18 - 25 °C.

Dilution Adhesin A 8162-22 can be diluted with cold water if required.

Cleaning Uncured adhesive residues as well as dried adhesive films can easily be removed with hot water. Wetting agents accelerate the cleaning process.

Disposal See Safety Data Sheet

Protective Measurements See Safety Data Sheet

Storage Conditions/ Shelf life

In closed original packaging 6 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost. Close containers carefully after use.

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.
Düsseldorf, April 2002

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad
Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050
Email: info@van-asperen.nl www.van-asperen.nl



Technologies
Industrial Adhesives