

# AQUENCE FB 7362

Known as Adhesin A 7362  
March 2013

## PRODUCT DESCRIPTION

AQUENCE FB 7362 provides the following product characteristics:

<b>Technology</b>	Synthetic Resin Dispersion
<b>Product Type</b>	Dispersion containing plasticizer
<b>Application</b>	Packaging Industry

## Application Areas

Folding Boxes: Side seam gluing

Bonding of lacquered (UV and dispersion lacquers) as well as treated PE- and OPP-film laminated papers and cardboards.

Window Patching:

Window-patching with PS-, PE- and OPP-films, also suitable for PE-coated board.

A surface treatment of at least 38 mN/m is necessary.

## Film Properties

- elastic
- slightly yellow

## Technical Data

### AQUENCE FB 7362:

Viscosity, Brookfield - RVT, 2/20/23, mPa.s	750 to 1,050
ISO 2555	
pH value	7 to 10
ISO 976	

## Compliance with food packaging regulations

Under specific conditions, AQUENCE FB 7362 is suitable for the manufacture of food packaging materials under the applicable FDA, EC-provisions and/or BfR recommendations.

A food contact statement with further details is available on request.

The responsibility for compliance with the specific conditions is with the converter and not with the adhesive supplier.

## DIRECTIONS OF USE

### Preliminary Statement

Prior to application it is necessary to read the Safety Data Sheet for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

## Application

Application method:

- nozzle

## Processing

Avoid direct contact with copper & bronze.  
Most suitable processing temperature: 18 - 25 °C.

## Dilution

AQUENCE FB 7362 is ready to use.

## Cleaning

Uncured adhesive residues can easily be removed with water. Wetting agents accelerate the cleaning process.

## Handling Information

Due to the variety of different materials available on the markets pre-tests should be carried out.

## STORAGE

Protect from freezing.

Close containers thoroughly after use.

When stored in a dry and cool place in the original unopened containers shelf life is as follows.

## Shelf life

Shelf-life (in unopened original packaging), months	4
Recommended Storage Temperature, °C	15 to 25

## Classification:

Please refer to the corresponding **safety data sheets** for details on:

**Hazardous Information**  
**Transport Regulations**  
**Safety Regulations**

## ADDITIONAL INFORMATION

### Disclaimer

#### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

#### **In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

#### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

## Reference 0.0

Wij stellen onze deskundigen beschikbaar om afnemers te helpen de beste resultaten met onze producten te bereiken. Aanbevelingen zijn gebaseerd op onderzoeken en ervaringen, die wij betrouwbaar achten. Aangezien wij echter geen controle hebben op de omstandigheden waaronder onze producten worden vervoerd, opgeslagen en verwerkt door onze afnemers, kan onzerzijds geen garantie gegeven worden voor bepaalde resultaten en kan ook geen aansprakelijkheid worden aanvaard voor schade, direct of indirect voortvloeiende uit de toepassing. Onze vertegenwoordigers zijn niet gemachtigd deze bepalingen te wijzigen of te herroepen.