

AQUENCE GL 702 ETICOL

Known as Eticol 702
March 2013

PRODUCT DESCRIPTION

AQUENCE GL 702 ETICOL provides the following product characteristics:

Technology	Casein
Application	Labeling
Appearance	yellow high viscosity liquid

Application Areas

- Glass bottle labeling
- coated glass
- uncoated glass

Product Properties

- High condensation water resistance
- High mileage, can be applied with low coating weight
- Fast setting

Technical Data

AQUENCE GL 702 ETICOL:

Solids Content, %	38.5 to 42.5
Viscosity, Brookfield - 23 °C, mPas Spindle 29, speed 5 rpm,	60,000 to 95,000

Typical Properties:

Tack	very high
Setting Time	fast
Open Time	long

DIRECTIONS OF USE

Preliminary Statement

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Application

All vertical roll labeling machines.
Recommended running temperature: 24 to 28 °C

Dilution

AQUENCE GL 702 ETICOL is ready to use and shall not be diluted.

Cleaning

Uncured adhesive residues can easily be removed with water.

STORAGE

Rotate stock, using oldest material first.
Protect from freezing.
Keep container covered when not in use to prevent moisture loss and contamination.
Do not mix with other adhesives.

Shelf life:

Shelf-life (in unopened original packaging), months 6
Refer to expiry date on original packaging.

Frost-Sensitive Yes
Recommended Storage Temperature, °C 10 to 30

Classification:

Please refer to the corresponding **safety data sheets** for details on:

Hazardous Information
Transport Regulations
Safety Regulations

ADDITIONAL INFORMATION**Disclaimer****Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0

Wij stellen onze deskundigen beschikbaar om afnemers te helpen de beste resultaten met onze producten te bereiken. Aanbevelingen zijn gebaseerd op onderzoeken en ervaringen, die wij betrouwbaar achten. Aangezien wij echter geen controle hebben op de omstandigheden waaronder onze producten worden vervoerd, opgeslagen en verwerkt door onze afnemers, kan onzezijds geen garantie gegeven worden voor bepaalde resultaten en kan ook geen aansprakelijkheid worden aanvaard voor schade, direct of indirect voortvloeiende uit de toepassing. Onze vertegenwoordigers zijn niet gemachtigd deze bepalingen te wijzigen of te herroepen.

