

Product Data Sheet

ETICOL 425

114-049A



0608/SA/03

Description

Formulated casein adhesive

Appearance

Off-white, high viscosity liquid

Technical Characteristics

Typical Data

Viscosity Brookfield
(Sp29, 5 rpm)

80,000 mPa.s @ 23°C

Solids

40.3 %

pH

8.5

Typical Applications

* Glass Bottle Labelling

Typical Properties

Tack : Medium

Set Speed : Medium-Fast

Open Time : Long

The information given and the recommendations made herein are based on our experience and are believed to be accurate. No guarantee as to, or responsibility for, their accuracy can be given or accepted and no statement made herein is to be treated as a representation or warranty. In every case we urge and recommend that purchasers before using any product make their own tests to determine, to their own satisfaction, its suitability for their particular purposes under their own operating conditions. Such as evaluation should be repeated if materials are changed in any way or bought from a different source. No agent or representative of our has any authority to vary, omit or otherwise alter these terms.



Features

- * Good ice-proof properties
- * Medium tack
- * Good caustic removability

Benefits

- * High level of security where labelled bottles are exposed to ice cold water.
- * Will run at low coat weights providing securely labelled bottles. Suitable for foiling applications.
- * Suitable for returnable bottle applications

Application Guide

All vertical roll labelling machines

Suggested running temperature: 24 - 28°C

Clean-up of equipment with warm (~40°C) water.

Packaging

Consult local sales office

Storage & Handling

Rotate stock using oldest material first.

Keep covered to prevent contamination and drying out.

Do not mix with other adhesives.

Protect from freezing.

Shelf Life: For best results, use within 4 months from date of manufacture.

HEALTH & SAFETY

Users should familiarise themselves with the safety data sheet before using or handling this product.

The information given and the recommendations made herein are based on our experience and are believed to be accurate. No guarantee as to, or responsibility for, their accuracy can be given or accepted and no statement made herein is to be treated as a representation or warranty. In every case we urge and recommend that purchasers before using any product make their own tests to determine, to their own satisfaction, its suitability for their particular purposes under their own operating conditions. Such as evaluation should be repeated if materials are changed in any way or bought from a different source. No agent or representative of our has any authority to vary, omit or otherwise alter these terms.