

Technical Data Sheet



Super-Lok 260

<u>Product type</u>	Formulated synthetic emulsion adhesive
Application	Cigarette Industry General packaging Adhesive
<u>Physical properties</u>	
Viscosity	Approx. 3,000 mPa s BROOKFIELD RVT Sp.3,20 Rpm,23°C
pH	4.5
Solids	55% 30 min,130°C
<u>Characteristics</u>	
Colour	white
<u>Processing</u>	
Application method	Apply by roller, wheel, contact and non-contact extruders, stencil and pen applicators.
Temperature	18-25°C
Cleaning	Not dried glue can be easily removed by cold water
Waste disposal	Refer to safety data sheet
<u>Packaging</u>	Consult local Sales Office
<u>Safety reference</u>	Refer to safety data sheet
<u>Storage</u>	Rotate stock using oldest material first. Keep covered to prevent contamination and drying out. Stir thoroughly before use. Do not mix with other adhesives. Protect from freezing. Shelf life: For best results use within 3 months from day of delivery.

This information is based on our latest researches and experiences. They however don't dispense from previous tests with the concerned substrates.

02.03.2009

Van Asperen Kleefstoffen B.V. Vaartweg 106 8243 PP Lelystad
Tel: +31 (0) 320-260261 Fax: +31 (0) 320-260050
Email: info@van-asperen.nl www.van-asperen.nl

