

Technical Information

Adhesin TH



Type of adhesive	emulsion-based adhesive without plasticizer	
Field of application	Manufacture of Bags and Pouches Bottom glueing of unlacquered papers.	
Product specification		Test Method
viscosity	120.000 \pm 20.000	Brookfield RVT, 7/20/23 ISO 2555
pH-value	7,5 \pm 1,0	ISO 976
Properties	Adhesin TH has a long open time and therefore large surface bondings can easily be corrected.	
Processing	Adhesin TH corresponds to FDA 175.105.	
Application	roller, top glue applicator Optimum working temperature: 18 - 25 °C.	
Dilution	Adhesin TH can be diluted with cold water if required.	
Cleaning	Uncured adhesive residues can easily be removed with water. Wetting agents increase the cleaning process.	
Disposal	see Safety Data Sheet	
Protective Measures	see Safety Data Sheet	
Storage Conditions/ Shelf Life	In closed original packaging 12 months from date of production. Optimum storage temperature: 15 - 25 °C, protect from frost. Close containers thoroughly after use.	

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.
Düsseldorf, May 2003