



Henkel

## Complete High-Performance Adhesive Product Range Based on Natural Polymers for all Labeling Needs

### Your Benefits

- High processing and bonding quality
- Efficient consumption
- Broadest portfolio & technology selection
- Excellent machinability
- Top quality and reliability for all your labeling applications
- Environmentally sustainable





**Henkel**

**Eticol®**

**Always the Right Product Solution for all Seasons**

	Application	Viscosity	Wet tack	Setting speed	Optimum operating temp.
<b>Eticol® 425</b>	Versatile use, multi-purpose product, high performance, good IWR, foiling	80 000 mPas (Brookfield at 23 °C)	medium	medium	24 – 28 °C
<b>Eticol® 700</b>	High tack product, good flow properties combined with excellent machinability	70 000 mPas (Brookfield at 23 °C)	high	fast	15 – 30 °C
<b>Eticol® 701</b>	Versatile use, foiling, efficient consumption even on cold/wet bottles, fast setting	85 000 mPas (Brookfield at 23 °C)	medium	very fast	24 – 28 °C
<b>Eticol® 702</b>	Highest tack level, high performance product, highest CWR, economic consumption, problem solver	65 000 mPas (Brookfield at 23 °C)	very high	fast	24 – 28 °C
<b>Eticol® 706</b>	High performance product, highest IWR, fast setting	95 000 mPas (Brookfield at 23 °C)	very high	fast	24 – 30 °C
<b>Eticol® 710</b>	Versatile use, standard applications	75 000 mPas (Brookfield at 23 °C)	low	medium	24 – 30 °C

## Elements of Value

For information about our comprehensive service offering and how it can really help your business – please refer to our documents about Service, Process and Design opportunities or contact your local Henkel sales representative.



## Contact

**Henkel AG & Co. KGaA**  
 40191 Düsseldorf, Germany  
 Phone +49 211 797-4119  
 Fax +49 211 798-2312  
 Email [labeling@henkel.com](mailto:labeling@henkel.com)  
[www.henkel.com](http://www.henkel.com)